

Hydraulic Oil Coolers - Series AM

PILAN Shell and Tube Heat Exchangers are designed in a three passes tube stack arrangement with cooling fluid inlet and outlet in opposite sides and counter current fluids. Tube stack is fully floating type thus thermal stresses are minimised while maintenance operations are eased.

PILAN® range of Marine Shell & Tube Heat Exchangers are suitable for any sort of heat transfer fluids, heating or cooling process fluids. Its use is restricted to liquid phase fluids and material compatibility should be observed.

MAWP: oil 14 bar, water 10 bar * MAWT: 120°C (180°C with VITON seals)


* Testing Standard: BS6755 Stability Test performed at 20 bar, Sealing Leakage Test at 14 bar.



Dimensions

Model	A	B	C	D	E-F	Weight
TP-A1M	195	72	38	Ø86	3/4"	3
TP-A2M	263	138	103	Ø86	3/4"	3,5
TP-A3M	349	225	189	Ø86	3/4"	4
TP-A4M	448	326	288	Ø86	3/4"	4,7
TP-A5M	576	450	415	Ø86	3/4"	5,5


Length Units expressed in mm, Diametres in Inches / Weight in Kgs
General Arrangement Drawings pdf or Auto-Cad formats are available on request.




Parts and Materials

Part	Name	Material
1	Shell	Aluminium /Bronze/Cast Iron
2	Tube Stack	
2.1	Tubes	Copper-Nickel / St. Steel / Copper
2.2	Tube plates	Brass / Bronze
2.3	Baffles	Aluminium
2.4	Welding	Tin welded 60/40
3	End caps	Brass / Bronze
4	Seals	NBR / Viton
5	Cover screws	Steel
6	Drain plugs	Brass

Remarkd materials denote standard construction for Marine Units.



Performance Graphs



Graphs were plotted using the parametres shown in the right side table.
For oil pressure drop graphs see separated sheet.

Flow Rate

Model	Heat dissipated (kW)	Oil flow (l/min)	Water flow (l/min)	Oil pressure drop (bar)	Water pressure drop (bar)	Surface (m2)
TP-A1M	3	30	15	0,10	0,02	0,13
TP-A2M	6	46	23	0,19	0,05	0,22
TP-A3M	9	56	28	0,36	0,09	0,32
TP-A4M	13	64	32	0,60	0,13	0,46
TP-A5M	16	56	28	0,56	0,12	0,68

Maximal Fresh Water Flow Rate Capacity: 50 l/min (35 l/min if sea water). This table means a typical performance of the shown units at given average process data of oil outlet temperature : 50°C; Water Inlet Temperature: 25°C, Viscosity of Oil: 38Cst with SAE 30 type and 50°C. Any other change in the chosen parametres could result in a different oil cooler selection.

Temperature Correction Factors

When temperature gap between oil outlet and water inlet exceeds the given 25°C the following correction factors should be used:
10°C: 0.4 / 15°C: 0.6 / 20°C: 0.8 / 30°C: 1.2 / 35°C: 1.4 / 40°C: 1.6 (multiply KW by the suitable correction factor).

Flow Rate Correction Factors

For water flow rates other than 50% of the oil flow rate, the following correction factors should be used:
25%: 0.8 / 100%: 1.2 (multiply the flow rate by the suitable correction factor).